GROUP–B











ENLARGED VIEW OF SERRATION

FOR INSPECTION AND OTHER PARAMETERS RFI.SK.-6274, DATED-14.06.96 TO BE FOLLOWED.

THIS IS A LESS STRESSED ITEM(GROUP–B)

NOTE:–
1) DIMNS. WITH TOLERANCE TO BE MAINTAINED.
2) TOLERANCES ON UNTOLERATED DIMENSION3±0,13.
3) FINISH DIMENSIONS ARE GIVEN SURFACES MUST BE SMOOTH FINISH.
4) CASTING TO BE SUPPLIED IN ANNEALED CONDITION TO A HARDNESS OF 200–230 HB MAX.
5) THE CASTING SHOULD ATTAIN HARDNESS 450–620 H.V. AFTER HEAT TREATMENT (SAMPLES TO BE SUBMITTED)
6) MARK 'IC' SUITABLY AS SHOWN.
7) 100% INVESTMENT CASTING IS TO BE SUBJECTED FOR RADIOGRAPHIC TEST INITIALLY FOR ADVANCE SAMPLES OF 15 NOS. AND THERE AFTER AT LEAST 3% RADIOGRAPHIC TEST SHOULD BE FOLLOWED AS PER :-ASTM-E-192-84 LEVEL-1.

MATERIAL SPECIFICATION:–
1) BS: 3146 PART 1:1974 TYPE CLA-12 GRADE 'C'
2) DECARBURISATION SHOULD NOT EXCEED MORE THAN 2% OF THE BASIC SIZE (CLAUSE 1.9 OF BS:3146 PT.1:1974).

PRECISION CAST

† RFI.SK.NO. 3571 #3

MATERIAL	ALL DIMENSIONS ARE IN MILLI METRE. IMPORTANT DIMENSIONS MARKED THUS ● INFORMATION MARKED THUS † TO BE MEASURED ON			
TITLE OF	OPERATION	2005	NAME	DATE
CATCH SAFETY (T.C)		RE, DRN.	R.CHAKRABORTY	6-9-2005
ORDNANCE FACTORY BOARD RIFLE FACTORY ISHAPORE	SCALE 2:1 (10:1)	CKD.		7/9/05
		APPD.		

PISTOL AUTO 9mm1A
CATCH SAFETY
CISA/333/12/4, DS.CAT.–1005–003152

DRG. NO.
RFI. SK. NO. 3571 #3
SHEET– OF–

DESCRIPTION	DRG. NO.
[illegible]	88/88
[illegible]	118/01
[illegible]	218/88
[illegible]	106/88
[illegible]	106/88
[illegible]	106/88

TITLE, NOTE AMENDED & DRG. NO. ADVANCED TO RFI.SK 3571 #3 — 02/01/10 Dt. 7/1/10

NOTE-(IX)
CASTINGS SHALL BE EXAMINED FOR FREEDOM OF SURFACE DEFECT BY:– MAGNETIC PARTICLE INSPECTION.
THIS HAS REFERENCE TO:–
COA (MET) NO. MQA–1/KPL/10/S.20.2.92. DT. 23.3.92.
COA (SA) NO. 1/PC/4/6. DT. 23.3.92.

VETTED VIDE LETTER NO. ISA/T/04 DT. 23.9.81. THIS DRG. IS VETTED IN RESPECT OF MATERIAL BY TSI VIDE ISA LETTER NO. ISA/TS/1, DT. 22-4-88

JWM|MPM

19-07-20

#129