


	DIMN. 'A'
7.62 m.m.	12.00 ^{±0.13}
5.56 m.m.	11.00 ^{±0.13}



MATERIAL :- JSS 9535-2 (COLD ROLLED QUARTER HARD)
HARDNESS :- 70-95 V.P.N. AT 10 KG. LOAD.

3577	16.5.13	'H'	WM/TR
2626	123.02	'G'	JGM/TR
798	3.5.91	'F'	Sd/- AWM/DO
780	23.11.90	'E'	Sd/- WM/DO
779	26.10.90	'D'	Sd/- WM/DO
707	16.12.87	'C'	Sd/- WM/DO
505A	31.12.82	'B'	Sd/- WM/DO
274	4.2.75	'A'	Sd/- ME
NO.	DT.	ALT.	SIG.

NOTES

1. UNSPECIFIED TOL. AS PER IS : 2102 (MEDIUM CLASS)
2. TO BE SUPPLIED IN COILS OF ARBOR DIA. 115 mm. (APPROX.) & EXTERNAL DIA. 255-365 mm.
3. EDGEWISE CURVATURE (HEIGHT OF CHORD) : 76 mm (MAX.) IN ANY 1830 mm LENGTH.
4. TENSILE STRENGTH IS NOT CONSIDERED AS AN ACCEPTANCE CRITERIA.

FOR GENERAL MANAGER

2002	DATE	NAME	PROJECTION	ORDNANCE FACTORY
JWM/TR	13 03	Wm	3 RD ANGLE	<u>VARANGAON</u>
CHD				
DRN	12-3	P.M.R.		
SCALE :- 1:1			BRASS STRIP FOR 7.62 m.m. & 5.56 m.m. PRIMER ANVIL	
DIMENSIONS ARE IN MM				
			SHEETS - 1 SHEET NO. - 1	DRG. NO. - V/PROD/0038 H