
R11
R10 FOR ALL RADIUSES, UNLESS OTHERWISE SPECIFIED.
R10 для всех прилибов, кроме особо оговоренных
THE REST OF RISER
Остаток прибыли 4
А–А
Развернуто
DEVELOPED
1. UNSPECIFIED TOLERANCES OF ROUGH DIMENSIONS AND THICKNESS OF WALLS ±2 mm.
2. DRAFT NOT MORE THAN 1:20 TOWARDS EXTERNAL SIDE.
3. UNSPECIFIED CASTING RADII SHOULD BE CARRIED OUT R20 ÷ 30.
4. MATERIAL SHOULD BE MARKED AS PER GOST 2171-75 ON ANY NON OPERATING SURFACE BY PUNCHING. STEEL OF TYPE 20-5 GOST 2630-62.
5. CASTING SHOULD COMPLY WITH GENERAL PARTS OF 172 T16 FOR NON FERROUS CASTINGS.
6. TOLERANCE FOR ALLOWANCE +2 -1
Б–Б
Вид Б
(Повернуто)
VIEW Б
(TURNED)
В–В
Е–Е
(Повернуто)
(TURNED)
172.28.002-1
CASTING
CASE
ADOPTED
Group 172 T-5
PROF-PARCERS 1
SHEET 1 of 3
MASS
SCALE 1:1
MATERIAL: AL 9, GOST 2685-75
HEAVY VEHICLES FACTORY
AVADI
DATE
REFERENCE
DRAWN
CHKD
APPD