



**FINISH:** TO BE SMOOTHLY FINISHED WITHOUT ANY SHARP EDGES  
 NICKLE-CHROMIUM PLATED TO IS: 1068-1968, SERVICE GRADE No.3,  
 (5 Ni 40 b cr y)

**PROOF LOAD (P):** 250 kgf

*APPROVED*  
*[Signature]*

Q	15-12-99	D-3	ADRDE/PAS/AEP/ 57/B, DT. 13-12-99	PROOF LOAD DIRECTION INDICATED	Joh	skant
R No	DATE	ZONE	AUTHORITY	BRIEF RECORD	O/C DES	HEAD QA
DRN	Sattar/Khy		DRD	MATERIAL: CARBON SPRING STEEL EN-42 AS PER BS: 970-1955	ADRDE, AGRA	
CHD	202/111		Joh	FINISH: AS SPECIFIED ABOVE		
TRD			O/C	HARDNESS: - HV 375-400	APPROVED.	
COMP			P.G.D			
SCALE: 1:1			PROJ. OFFICER DIV. HEAD		PROG. DIRECTOR (QA) DRG No. (a) ADRDE/1301 DRD/43/98	
DIMENSIONS ARE IN mm			CONNECTING LUG OF AUXILIARY PARACHUTE			
TOLERANCE IS: 2102 (PEI) MEDIUM						

F PACKING CLAUSE:- <sup>α</sup>

EACH CONNECTING LUG SHALL BE PACKED IN A POLYTHENE BAG OF SUITABLE SIZE AND TIED THE MOUTH OF THE BAG TO BE HEAT - SEALED 20 NOS. THIS SEALED BAG SHALL BE PACKED IN A SUITABLE SIZE OF CARTON 10 NOS. OF SUCH CARTONS SHALL BE PACKED IN A C.W.P (DULY LINED WITH PAPER PACKING WATER PROOF) ONE CONNECTING LUG IN EACH CARTON SHALL BE IDENTIFIED BY A LABEL SHOWING CAT. NO, DESIGNATION OF THE STORE AND ALSO THE RECOGNISED INITIALS OF THE - MANUFACTURER. THE PACKING CASE SHALL BE LEGIBLY AND INDELIBLY MARKED WITH THE ADDRESS OF THE CONSIGNEE, CONSIGNOR, CAT. NO, NOMENCLATURE OF THE STORE, THE YEAR OF MANUFACTURE, TOTAL NO OF PACKING CASES AND THE NO. OF INDIVIDUAL PACKING CASE IN A CONSIGNMENT

APPROVED  
*[Signature]*

α 15/12-99		F-4	ADRDE/PAS/AEP/57/B, DT. 13-12-99	PACKING CLAUSE INCLUDED AS SHEET No. 2		<i>[Signature]</i>	<i>[Signature]</i>	
R.No	DATE	ZONE	AUTHORITY	BRIEF RECORD			CVC DTS	HEAD (Q.A)
SCALE	ADRDE, AGRA			DRN	<i>[Signature]</i>	PROJ. OFFR		
DIMENSION IN mm.	GROUP:			CHD	<i>[Signature]</i>	GROUP DIR		
TOL.	CONNECTING LUG OF AUXILIARY PARACHUTE			<i>[Signature]</i> OKC D&S				
MATERIAL PROCESS:-				APPROVED				
FINISH:-				<i>[Signature]</i>				
HEAT TREATMENT:-				HEAT (Q.A)				
				DRG. NO	ADRDE/1301			
				PROV NO	DRD/43/98			