(i) JUNCTION BOX SS 304,EX ENCLOSURE 200 X 250 X 121MM WITH SCREW LID LOCKING ARRANGEMENT,SS MOUNTING PLATE,MOUNTING BRACKET HAVING NATURAL BUFF FINISH,-20TO +40 DEG.C,IP 66 CERTIFIED, ASSEMBLED WITH FOLLOWING COMPONENTS.DIN RAIL TS 35/7.5-0.66M,SELECTOR SWITCH 0-1,2 POSITION WITH1NO+1NC,COLOURBLACK,SCREW TERMINALS ST 2.5 COLOUR GRAY PHOENIX-25 NOS.END PLATES PHOENIX,END CLAMPS PHOENIX,MARKERS PHOENIX.SCREW TERMINALS ST 2.5 PHOENIX. Qty. 32 nos.

(ii) JUNCTION BOX SS304,EX ENCLOSURE 330X300X121MM WITH SCREW LIDLOCKING ARRANGEMENT,SS MOUNTING PLATE,MOUNTING BRACKET HAVING NATURAL BUFF FINISH,-20 TO +40 DEG.C,ASSEMBLED WITH FOLLOWING COMPONENTS.DIN RAIL TS 35/7.5-0.66M,SCREW TERMINALS ST2.5 COLOUR GRAY PHOENIX-75 NOS. END PLATESPHOENIX,END CLAMP PHOENIX,MARKERS PHOENIX,SCREW TERMINALS ST 2.5 PE PHOENIX. Qty. 48 nos.

(iii) JUNCTION BOX SS304,EX ENCLOSURE 200X250X121MM WITH SCREW LID LOCKING ARRANGEMENT,SS MOUNTING PLATE,MOUNTING BRACKET HAVING NATURAL BUFF FINISH, -20 TO+ 40 DEG.C,IP 66 CERTIFIED,ASSEMBLED WITH FOLLOWING COMPONENTS,DIN RAIL TS 35/7.5-0.66M,SCREW TERMINALS ST2.5 PHOENIX-25NOS,END PLATES PHOENIX,END CLAMPS PHOENIX,SCREW TERMINALS ST2.5 PE PHOENIX. Qty. 64 nos.