

HOUSING SLING


MATERIAL: STEEL IS: 7226 C40

HARDNESS: 250- TO 300 H.V.

PROTECTIVE FINISH: PHOSPHATED TO JSS-0465-01-1988

CLASS-II (ACCELERATED) DIL FINISH

DIMENSIONS ARE IN M. M.
INFORMATION MARKED THUS 't' TO BE MARKED ON
UNTOLERATED DIMENSIONS AS PER IS. 2102 (MEDIUM)

ITEM NO.	DESCRIPTIONS	NO OFF	MATERIAL	TREATMENT	REMARKS
	 SIGNATURE & DATE DRAWN: <i>J. Venkatesh</i> CHECKED: _____ TRACED: _____ TRACING CHECKED: _____ I/C DESIGN & DRG. OFFICE: <i>J. Venkatesh</i>				SUB: <u>HOUSING SLING</u> FOR: <u>SLING</u> OF: <u>40mm MQL</u> DES. REF NO: <u>DS. CAT. NO. 1005-0080-32 (R8331CES)</u> DRG. NO: <u>307 1700 022 A3</u>
	AMENDMENTS	SIGNATURE & DATE	APPROVED ON: <u>14/8/12</u>	DIVISIONAL OFFICER	SCALE: <u>NTS</u> STORE DRG NO: _____ OPERATION NO: _____ SHEETS: <u>7</u> SHEET NO: <u>7</u>



ORDNANCE FACTORY,
TIRUCHIRAPALLI.