



SECTION-AA

PROOF LOAD:- 130 kgf

PACKING :-

EACH CLASP SHALL BE PACKED IN A POLYTHENE BAG OF SUITABLE SIZE AND TIED THE MOUTH HEAT SEALED. 20 NOS. SHALL BE PACKED IN A SUITABLE SIZE CARTON. 10 NOS. OF SUCH CARTON SHALL BE PACKED IN A C.W.P (DULY LINED WITH PAPER PACKING WATER PROOF). ONE CLASP IN EACH CARTON SHALL BE IDENTIFIED BY A LABEL SHOWING CAT. NO., DESIGNATION OF THE STORE AND ALSO THE RECOGNISED INITIALS OF THE MANUFACTURER. EACH CARTON SHALL BE MARKED WITH THE INITIALS OF THE MANUFACTURER. THE PACKING CASE SHALL BE LEGIBLY AND INDELIBLY MARKED WITH THE ADDRESS OF THE CONSIGNEE, CONSIGNOR, CAT NO, NOMENCLATURE OF STORE, THE YEAR OF MANUFACTURE, TOTAL NO. OF PACKING CASES AND THE NO. OF INDIVIDUAL PACKING CASE IN THE CONSIGNMENT.

Q. 23-10-01/23.4-C PAS/240/7		CHANGE IN DIMENSIONS		Pudi		
RNO	DATE	ZONE	AUTHORITY	BRIEF RECORD	O/C D&S	HEAD G.A.
DRD	AK Solanki	DRD		MATERIAL - M.S WIRE AS PER SPEN IS. 286-1972	ADDRDE AGRA	
CHD	372-11-98	Jsl	24-11-98	FINISH - TO BE SMOOTHLY FINISHED & CO. PLATED AS PER IS 1572 TO MINIMUM THICKNESS OF 0.012 mm.		
TRD		O/C	PGD	HARDNESS:-	APPROVED.	
COMP		PROJ OFFR	PGD	AVERAGE 150/160 B.H.N.		
SCALE - 1:1		DIV HEAD			PROG DIRECTOR (Q.A)	
DIMENSIONS ARE IN MM	CLASP FOR MAIN SLEEVE					
TOLERANCE IS: 2102 (PE-1) MEDIUM	FOR PSM SERIES				DRG NO ADRDE/1327 (9)	