



NOTES :-

1. ALL DIMENSIONS ARE IN mm. -0.06
2. THE ~~THICKNESS~~ THICKNESS OF THE POLYTHENE BAG SHOULD BE 0.26 mm.
3. THE FILM SHOULD BE FREE FROM ANY OBJECTIONABLE ODOUR
4. THE FILM SHOULD BE UNIFORM IN COLOUR, TEXTURE & FINISH. THE MATERIAL SHOULD BE SUBSTANTIALLY FREE FROM PIN HOLES, UNDISPERSED RAW MATERIALS, STREAKS AND PARTICLES OF FOREIGN MATTER. THERE SHOULD NOT BE ANY OTHER VISIBLE DEFECTS, SUCH AS HOLES, TEARS OR BLISTERS. THE EDGE SHOULD BE FREE FROM NICKS AND CUTS VISIBLE TO UNARMED EYE. THE NATURAL FILS SHOULD BE FREE FROM PIN HOLES.

MATERIAL SPECIFICATION : L.D.PE. GR.
 TYPE-1 TO SPECN. JSS 9330-03 : 2007 REV. No. 2

JWM/MCC

SR. NO.	DATE	BRIEFS NOTES		SIGN.	APPVD	SCALE	DATE	PROJ.	SHT. NO.
		AMENDMENTS							
③	12.10.12	THICKNESS WAS 0.2 MINIMUM. LATEST JSS SPECN. ADDED.		<i>[Signature]</i>					
②	12.9.11	Dim of A 440 was 3.45 & 3.55 Amend in the Dim of 3.45 misc sec of 9/9/11		<i>[Signature]</i>					
①	14.2.11.	MATL. SPECN. : L.D.PE. GR. 'A' WAS GRADE 'A', REF. : O.F.A / STD / 2708 / SIS VET / 84MM CG, DT. : 02.2.11.		<i>[Signature]</i>					
ORDNANCE FACTORY, AMBARNATH									
POLYTHENE PROTECTIVE BAG									
FOR CARTG. CASE 84 MM									
CARL GUSTAV									
DRG NO : CG84/SK / 11003/IG									
NTS 14.11.10 3rd Δ 1 OF 1									