

ANNEXURE - VI

CLOTH POLYESTER & COTTON DISRUPTIVE PATTERN (220 GSM) FOR JUNGLE WITH ARMY LOGO 152 CMS (MINIMUM) EXCLUDING SELVEDGES, SPECN NO: PROV/OCFAV/FABRIC/005 AND THAT

- 1) IN APPEARANCE, FEEL, FINISH AND ALL OTHER RESPECTS INCLUDING SHADE, MATERIAL SHALL CONFORM TO CORRESPONDING SEALED SAMPLES HELD IN THE CUSTODY OF CONTROLLER CUSTOMER SERVICE CENTRE, OCE., AVADI.
- 2) BLEND COMPOSITION SHALL BE COTTON - 80%+/-3%.
POLYESTER - 20%+/-3%.
- 3) FIRM SHALL GET THEIR NAME WOVEN IN THE SELVEDGE WITH FINER THREAD OF SAME COLOUR AT AN INTERVAL NOT EXCEEDING 30 CMS BETWEEN TWO MARKINGS.
- 4) FABRIC SHALL BE WOUND IN SUCH A WAY THAT, DURING OPENING UNWINDING OF FABRIC ARMY LOGO SHOULD BE ORIENTED IN UPWARD DIRECTION ON ALL THE ROLLS.
- 5) WIDTH OF SELVEDGE SHALL NOT EXCEED 8 MM.
- 6) THE MANUFACTURER SHALL SUPPLY THE MATERIAL DULY FLAGGED FOR ALL TYPE OF DEFECTS.
- 7) PACKING & MARKING: AS PER CQA(T&C) KANPUR SCHEDULE NO. CQA(T&C)/PMS/35(D), EXCEPT THAT
 - A) FABRIC IN ROLL FORM SHALL NOT BE LESS THAN 40 METERS IN RUNNING LENGTH WITHOUT STITCHING/BASTING IN BETWEEN
 - B) ROLL WEIGHT SHALL NOT EXCEED 50 KGS.
 - C) EACH ROLL OF FABRIC SHALL BE WRAPPED SEPARATELY WITH POLYPROPYLENE PLAIN SHEET. FINAL PACKING OF 1 ROLL IN ONE WATER PROOF GUNNY/HDPE SHEET.
 - D) DIMENSIONS FOR PAPER TUBES OF FABRIC ROLL:
OUTER DIA - 3.5 CM, INNER DIA - 2.5 CM.
THICKNESS - 0.5 CM.
 - E) FABRIC SELVEDGES SHALL BE WOUND EVENLY AT ONE EDGE.
- 8) SELVEDGES SHALL BE FIRM, STRAIGHT AND FRINGES IF ANY SHALL NOT BE MORE THAN 5 MM.
- 9) SAMPLING PLAN: AS PER RELEVANT CLAUSE OF SPECIFICATION.
- 10) SHORT LENGTH PIECES BETWEEN 10M TO 40M SHALL BE SUPPLIED / ACCEPTED TO THE EXTENT OF 5% OF TOTAL ORDER QTY. SHORT LENGTH PIECES BETWEEN 10M TO 20M SHALL BE ACCEPTED WITH 12% PRICE REDUCTION TO COMPENSATE THE MATERIAL & LABOUR LOSS.

NETTED FOR
TECHNICAL PARTICULARS ONLY

HOS/TC