



SEC. A-A.

1. DEFECTION OF COLLIMATING RAYS IN NORMAL CONDITIONS SHOULD CORRESPOND TO THE REQUIREMENTS OF THE DRAWING AU 4.496.007C6. (MAIN ASSEMBLY)
2. THE RESISTANCE OF CURRENT CONDUCTING COATING SHOULD BE EQUAL TO THE VALUE SHOWN IN THE DRAWING AU 4.496.007C6.
3. DISPLACEMENT OF SURFACE 'B' OF HEATING PLATE 1, RELATIVE TO SURFACE 'B' OF PLATE 2, SHOULD NOT BE MORE THAN 1 M.M.
4. DIFFERENCE IN DIMENSIONS 'P' SHOULD NOT BE MORE THAN 2 M.M.
5. PROJECTING PORTION OF ADHESIVE FILM 3 SHOULD BE CUT ALONG THE PROFILE OF PLATES.
6. THE REST OF THE TECHNICAL REQUIREMENTS AS PER SPECS TY-3.31834-78
7. THE PRESENCE OF ADHESIVE FILM WITH THICKNESS UP TO 0.5 M.M. IS ALLOWED ON SURFACE 'X' ON 20% AREA OF SURFACE 'A' AND ON SINKING SURFACE 'B' OR 'B' CORRESPONDINGLY ON PROTRUDING SURFACE 'B' OR 'B' AND ON SURFACE 'U' THE TRACES OF UP TO 0.1 M.M. ARE PERMISSIBLE.

आद्युध निर्माणी ORDNANCE FACTORY देहरादून DEHRADUN	आदेशिका क्र. 174-99 आदेशिका क्र. 174-99 पदसूची क्र. 174-99	<b>GLASS SAFETY WITH ELECTRICAL HEATER, SE-15</b>		आदेशिका क्र. 174-99 आदेशिका क्र. 174-99 पदसूची क्र. 174-99	आदेशिका क्र. 174-99 आदेशिका क्र. 174-99 पदसूची क्र. 174-99
	अनुमोदित APPROVED अनुमोदित APPROVED	DRG. No <b>AU 5.803.003C6</b>	<b>GLASS SAFETY ASSY.</b>	आदेशिका क्र. 174-99 आदेशिका क्र. 174-99 पदसूची क्र. 174-99	आदेशिका क्र. 174-99 आदेशिका क्र. 174-99 पदसूची क्र. 174-99
	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED
	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED	अनुमोदित APPROVED अनुमोदित APPROVED