

Specification

SR.NO	ITEM CODE	NOMENCLATURE/SPECIFICATION	QTY.(In KG)
1	0329586050	ST.SQR.50 MM TO SPECN.BS:3S144:1995(1999) GD. S144 H TEST COND S144H.MATL. SHOULD BE PROCESSED THROUGH LFVD WITH CALCIUM SIL ICIDE TREATMENT SULPH.-0.15MAX,PHOS.-0.03MAX CHART SECONDARY REFINNING STEEL AS PER IS:4163-82,INCLUSION RATING SHOULD NOT EXCEED THE FOLLOWING LMT.THN./THK.SULPH:1.5-1,ALUMI:1.5- 1,SILII: 1.5-1,GLO OXIDE 2.0-1	532
2	0329552095	STEEL SQR 95MM TO SPECN BS:3S144:1995(1999) Gd. S144'D'. 100% UT TO BE CARRIED OUT. (A) THE MATL.SHOULD BE MACROSCOPI -CALLY SOUND TO THE LEVEL OF C1;R1;S1.(B)-THE MATL.SHOULD BE FREE FROM DEFECTS SUCH AS INTERNAL FLAWS,BLOW HOLES,CRACKS, LAP,LAMINATION DULY ULTRASONICALLY TESTED	158
3	0329585075	STEEL SQR.75 MM TO SPECN.BS:3S144:1995(1999) GD.S144 D, TEST CONDITION S144H.	104