DIMENTION MARKED ⊥ MUST BE CONCENTRIC WITH THE LONGITUDINAL AXIS.

DIMENTION MARKED * MUST BE SMOOTH AND FREE FROM CORRUGATIONS

TOLERANCE ON UNTOLERANCED DIMENTION FOR ONE DECIMAL PLACE ±1.3 FOR TWO OR MORE DECIMAL PLACE ±0.13

WALL THICKNESS OF CONE MAY VARY BETWEEN H 6.35 AND L 5.08 BUT MUST LIE WITHIN A TOLERANCE BAND OF ± 0.38 ON AN INDIVIDUAL CONE AND MUST BE MAINTAINED FOR THE LENGTH SHOWN THUS *



FOR EXPLANATION OF DIMENSIONING ETC, SEE ANGLE PROJECTION

DIMENSIONS ARE IN mm

MATERIAL *

STEEL B.S. 1449 : PT 1 / 1983 GRADE 1CHR 43/25 ALTERNATIVELY CONES MAY BE MANUFACTURED BY FORGING METHOD FROM STEEL BAR TO SPECN. B.S. 970 PT. 1 : 1983 GR 070 M 20

TRACED FROM ORIGINAL DRG. SEALED BY CQA (AMMN) PUNE D.C.I. 1848B-A (")

DATE	AUTHORITY	REVISION	SIGN
24.7.98	DC No. 34922-A	MATERIAL AMENDED RETRACED WITHOUT CHANGE PREVIOUS B.C.S.(1) NO. 18438-A, 26765-A, 27250-A, 28817-A, 29178-A, 30802-A, 30140-A, 31157-A, & 31480-A.	Sd/- SKG AHSP
24.9.75			Sd/- SKG D.O.

DRG SEALED :- 19-11-45

D.O.C.I (A)

ITEM	DESCRIPTION	NO. OFF	MATL
	CONE CHARGE, DEMOLITION NO. 11, 30 LB REF. DRG NO. D.2(L) 961/E/326 AHSP :- C I (A) KIRKEE		*

TREATMENT	REMARK		
1992 2001	SIGN	DATE	
DRN/TRC	Hardeep	6/6/2001	
CHD		9/7/6	
F/DO		3/7/6	
APPD		9/7	

SCALE N.T.S

ORDNANCE FACTORY BHUSAWAL

DRG NO. OFB/C/1443