DETAILS OF AMENDMENT.

SL NO	DATE	ZONE	DESCRIPTION	AUTHORITY	SIGN.
1	16-10-97	E/5, D/7 B/5	DIMNS. 125, 400, 660 & 710 WAS 55, 105, 365 & 415. PT. NO. 5, 6 & 7 NEWLY ADDED. DRG. NO. ADVANCED TO RFI. SK. NO. 6431 *	AS PER DISCUSSION WITH JWM/PL(RATES) & D.O. REPRESENTATIVES FOR DEV. OF PROPER SEALING.	
2	28-4-99	—	DRG. REVISED & DRG. NO. ADVANCED TO RFI. SK. NO. 6431 *	AS PER INSTRUCTION OF WM/QC.	
3	30-4-11	A/3	IN TITLE BLOCK FOR '315" SPORTING RIFLE READ 30-06, 0-22" L '315" SPORTING RIFLE VIDE D.C OBE/101/11 dt 30-04-11	AS PER DISCUSSION WITH HOS/EB2. HOS/E-2.D	
4	16-01-12	A/3	IN TITLE BLOCK 12 BORE PAG ADDED VIDE D.C NO. OBE/104/12 DT. 16-01-12	AS DISCUSSED WITH HOS/E-10 & HOS/C-2.D	

SCHEDULE OF PARTS

SL NO	DESCRIPTION	NO OFF	MAT'L	REMARKS
1	MAIN PIECE	1	AS STATED	YELLOW COLOUR
2	SIDE PIECE	2	— Do. —	— Do —
3	STRENGTHENING BAND	3	— Do —	— Do —
4	CARRYING HANDLE	2	ROPE NYLON STRETCHED 15 ϕ	— DO —
5	LEAK SEAL (STD)	4	PLASTIC	BLACK-COLOUR
6	ROPE (SEALING)	3	NYLON	WHITE
7	LEAK SEAL (STD)	12	PLASTIC	BLACK



SHAPE OF THE LEAK SEAL (PT. NO. 5 & 7)

NOTES :-

SPECIFIED PHYSICAL PROPERTIES :- RFI. SK. NO. 6431 *4

1) COMP STRENGTH - 375 kg
2) ABLE TO WITHSTAND 1 hr. VIBRATION OF 225 CYCLES/Min. AND 2·54 cm AMP.
3) ABLE TO WITHSTAND IMPACT ON ALL SIX SURFACES.
4) ABLE TO WITHSTAND INCLINED IMPACT AT 7 Km/hr WITH 40 kg.
#5) PRINTED INSCRIPTION (BLACK) ON TOP FLAP LETTER SIZE 25 mm.

BY AIR
CALCUTTA TO AIR PORT
TO :-
FROM :- THE GENERAL MANAGER
ISHAPORE RIFLE FACTORY (W.B.)

370 × 700

CERTIFIED COPY OF LAYOUT/GAUGE SCHEDULE AT THIS DATE. 16.05.17

ISHAPORE RIFLE FACTORY, ISHAPORE

MATL :- CPP HOLLOW CORRUGATED (SUN PAC SHEET)

ALL DIMENSIONS ARE IN MILLI METRE
IMPORTANT DIMENSIONS MARKED THUS ⊕
INFORMATION MARKED THUS † TO BE MARKED ON

TITLE OF	OPERATION	1997	NAME	DATE
		DGN.		
		DRN.		
ORDNANCE FACTORY BOARD RIFLE FACTORY ISHAPORE	SCALE :- N.T.S	CKD.		
		APPD.	J.W.M/D.O	

CPP HOLLOW CORRUGATED BOX FOR SP-70/1 (CAPACITY :- 5 SIR. 2S)

DRG No. RFI. SK NO 6431 *4