



NOTE:-

- 1) REMOVE BURRS FROM BORES
CURVE ALL SHARP EDGES
- 2) GALVANIZED AND CHROMATIZED
TO 20-30 μ m

MATL:-STEEL UTS 540 MPa (min)
YIELD STRENGTH 350 MPa (min)

DRG BASED ON Cat No. 1150 D S No. 14/5420-000124

| | | | | | | | | | |
|---|---|---|---|---|---|--------------------------------------|--|---------------------------------|--|
| A | 8 | 7 | 6 | 5 | 4 | DRN | DRG NOT TO BE SCALED | PERTAINS TO:- IMSA-0167&0168 | |
| | | | | | | TCD | | | ALL SHARP EDGES & CORNERS TO BE ROUNDED OFF |
| | | | | | | CHD | | | ALL DIMENSIONS IN mm, UNLESS OTHERWISE SPECIFIED |
| | | | | | | PSD | | | NOMENCLATURE |
| | | | | | | APPD | STRAP (CAT - 1150) | IMPD-0981 | |
| | | | | | | DATE | | | |
| | | | | | | TOLERANCE UNLESS OTHERWISE SPECIFIED | SCALE :- 1:2.5 | | |
| | | | | | | GEN DEC ANG | CONTROLLERATE OF INSPECTION ENGINEERING EQPT | | |
| | | | | | | MEDIUM IS: 2102 | | | |