

1.1	DETAIL SPECIFICATION FOR PACKING BOX FOR FUZE PDM-557 WITH EPE FOAM:- <table border="1"> <thead> <tr> <th data-bbox="280 268 397 331">Sr. No.</th><th data-bbox="397 268 1477 331">Specification Particulars</th></tr> </thead> <tbody> <tr> <td data-bbox="280 331 397 472">1</td><td data-bbox="397 331 1477 472">The packing box shall be made of LLDPE Linear Low- density Polyethylene LL36RA045UV having outer dimensions L412 x W361 x Ht197 $\pm$ 5 (inclusive of lid) & Inner dimension L324.5 x W273 x Ht 184 $\pm$ 5 (Unit of dimensions are in mm).</td></tr> <tr> <td data-bbox="280 472 397 573">2</td><td data-bbox="397 472 1477 573">The packing box shall have a hinged lid with outer dimension L412 x W361 x Ht 59.8 $\pm$ 5 and inner dimension L 324.5 x W273 x Ht 56.5 $\pm$ 5(Unit of dimensions are in mm)</td></tr> <tr> <td data-bbox="280 573 397 646">3</td><td data-bbox="397 573 1477 646">The lid shall open up to an angle of 94.8° to 100° with ϕ 1.63 x 301mm SS wire rope.</td></tr> <tr> <td data-bbox="280 646 397 814">4</td><td data-bbox="397 646 1477 814">Bottom & top of the packing box shall be lock with four powder-coated SS304 latches Fitted with ϕ 4.56x L 9.51 SS rivets with neoprene punch washer & 3 SS304 powder Coated hinges fitted with M6 x 20 nut bolt for open and closing of the case. (Unit of dimensions are in mm)</td></tr> <tr> <td data-bbox="280 814 397 877">5</td><td data-bbox="397 814 1477 877">Bottom of packing box should have provision of integrated handle.</td></tr> <tr> <td data-bbox="280 877 397 1052">6</td><td data-bbox="397 877 1477 1052">One spring- based retractable sturdy handle powder coated is to be provided on the front side for easy lifting and transportation & it is fixed by M6 x 25 SS304 nut Bolt & neoprene washer of dimension L115 x W56 x TK 1.52 mm(Unit of dimensions are in mm)</td></tr> <tr> <td data-bbox="280 1052 397 1152">7</td><td data-bbox="397 1052 1477 1152">The packing box shall be lined with PE foam in such a way that there is no relative Gap between the internal faces of box and external faces of foam</td></tr> <tr> <td data-bbox="280 1152 397 1226">8</td><td data-bbox="397 1152 1477 1226">The total weight of empty box shall not be more than 5.50 Kg.</td></tr> <tr> <td data-bbox="280 1226 397 1356">9</td><td data-bbox="397 1226 1477 1356">Box should have 12 Nos. of equi-spaced pockets in profil packing fitment for packing of Fuses & 2 pockets for packing of silica Gel Pouches (20mm x 10mm x 30mm) such that rattling of fuses is avoided.</td></tr> <tr> <td data-bbox="280 1356 397 1457">10</td><td data-bbox="397 1356 1477 1457">A screen- printed labeling on the package box for fuse PD M557 to be printed on the top surface of the case.</td></tr> <tr> <td data-bbox="280 1457 397 1558">11</td><td data-bbox="397 1457 1477 1558">The packing box shall confirm/comply to various required tests such as Environmental testing in cold chamber conditions for 24 hrs, drop test & stack load test etc.</td></tr> <tr> <td data-bbox="280 1558 397 1696">12</td><td data-bbox="397 1558 1477 1696">Antimicrobial additives will be used during manufacturing of tendered item to prevent the growth of algae, fungus and other microorganisms, especially during prolonged exposure to rainy and humid conditions.</td></tr> <tr> <td data-bbox="280 1696 397 1896">13</td><td data-bbox="397 1696 1477 1896">Tendered item is being procured first time by the buyer; hence, buyer has mentioned only basic requirements of the product along with provisional/tentative drawing. For more details, bidders are requested to attend the Pre-Bid meeting to be held at Ordnance Factory Dehu Road, Pune on 7th working day after publication of instant bid. All the queries/clarification regarding the instant bid will be entertained at the time of Pre-Bid meeting only.</td></tr> </tbody> </table>	Sr. No.	Specification Particulars	1	The packing box shall be made of LLDPE Linear Low- density Polyethylene LL36RA045UV having outer dimensions L412 x W361 x Ht197 $\pm$ 5 (inclusive of lid) & Inner dimension L324.5 x W273 x Ht 184 $\pm$ 5 (Unit of dimensions are in mm).	2	The packing box shall have a hinged lid with outer dimension L412 x W361 x Ht 59.8 $\pm$ 5 and inner dimension L 324.5 x W273 x Ht 56.5 $\pm$ 5(Unit of dimensions are in mm)	3	The lid shall open up to an angle of 94.8 $^{\circ}$ to 100 $^{\circ}$ with ϕ 1.63 x 301mm SS wire rope.	4	Bottom & top of the packing box shall be lock with four powder-coated SS304 latches Fitted with ϕ 4.56x L 9.51 SS rivets with neoprene punch washer & 3 SS304 powder Coated hinges fitted with M6 x 20 nut bolt for open and closing of the case. (Unit of dimensions are in mm)	5	Bottom of packing box should have provision of integrated handle.	6	One spring- based retractable sturdy handle powder coated is to be provided on the front side for easy lifting and transportation & it is fixed by M6 x 25 SS304 nut Bolt & neoprene washer of dimension L115 x W56 x TK 1.52 mm(Unit of dimensions are in mm)	7	The packing box shall be lined with PE foam in such a way that there is no relative Gap between the internal faces of box and external faces of foam	8	The total weight of empty box shall not be more than 5.50 Kg.	9	Box should have 12 Nos. of equi-spaced pockets in profil packing fitment for packing of Fuses & 2 pockets for packing of silica Gel Pouches (20mm x 10mm x 30mm) such that rattling of fuses is avoided.	10	A screen- printed labeling on the package box for fuse PD M557 to be printed on the top surface of the case.	11	The packing box shall confirm/comply to various required tests such as Environmental testing in cold chamber conditions for 24 hrs, drop test & stack load test etc.	12	Antimicrobial additives will be used during manufacturing of tendered item to prevent the growth of algae, fungus and other microorganisms, especially during prolonged exposure to rainy and humid conditions.	13	Tendered item is being procured first time by the buyer; hence, buyer has mentioned only basic requirements of the product along with provisional/tentative drawing. For more details, bidders are requested to attend the Pre-Bid meeting to be held at Ordnance Factory Dehu Road, Pune on 7 th working day after publication of instant bid. All the queries/clarification regarding the instant bid will be entertained at the time of Pre-Bid meeting only.
Sr. No.	Specification Particulars																												
1	The packing box shall be made of LLDPE Linear Low- density Polyethylene LL36RA045UV having outer dimensions L412 x W361 x Ht197 $\pm$ 5 (inclusive of lid) & Inner dimension L324.5 x W273 x Ht 184 $\pm$ 5 (Unit of dimensions are in mm).																												
2	The packing box shall have a hinged lid with outer dimension L412 x W361 x Ht 59.8 $\pm$ 5 and inner dimension L 324.5 x W273 x Ht 56.5 $\pm$ 5(Unit of dimensions are in mm)																												
3	The lid shall open up to an angle of 94.8 $^{\circ}$ to 100 $^{\circ}$ with ϕ 1.63 x 301mm SS wire rope.																												
4	Bottom & top of the packing box shall be lock with four powder-coated SS304 latches Fitted with ϕ 4.56x L 9.51 SS rivets with neoprene punch washer & 3 SS304 powder Coated hinges fitted with M6 x 20 nut bolt for open and closing of the case. (Unit of dimensions are in mm)																												
5	Bottom of packing box should have provision of integrated handle.																												
6	One spring- based retractable sturdy handle powder coated is to be provided on the front side for easy lifting and transportation & it is fixed by M6 x 25 SS304 nut Bolt & neoprene washer of dimension L115 x W56 x TK 1.52 mm(Unit of dimensions are in mm)																												
7	The packing box shall be lined with PE foam in such a way that there is no relative Gap between the internal faces of box and external faces of foam																												
8	The total weight of empty box shall not be more than 5.50 Kg.																												
9	Box should have 12 Nos. of equi-spaced pockets in profil packing fitment for packing of Fuses & 2 pockets for packing of silica Gel Pouches (20mm x 10mm x 30mm) such that rattling of fuses is avoided.																												
10	A screen- printed labeling on the package box for fuse PD M557 to be printed on the top surface of the case.																												
11	The packing box shall confirm/comply to various required tests such as Environmental testing in cold chamber conditions for 24 hrs, drop test & stack load test etc.																												
12	Antimicrobial additives will be used during manufacturing of tendered item to prevent the growth of algae, fungus and other microorganisms, especially during prolonged exposure to rainy and humid conditions.																												
13	Tendered item is being procured first time by the buyer; hence, buyer has mentioned only basic requirements of the product along with provisional/tentative drawing. For more details, bidders are requested to attend the Pre-Bid meeting to be held at Ordnance Factory Dehu Road, Pune on 7 th working day after publication of instant bid. All the queries/clarification regarding the instant bid will be entertained at the time of Pre-Bid meeting only.																												