



SECTION-XX

PACKING NOTE :

EACH SAFETY PIN SHALL BE WRAPPED IN TISSUE PAPER & 25 Nos THIS WRAPPED BE PACKED IN A SUITABLE CARTON 10 SUCH CARTONS SHALL BE PACKED IN A G.W.P (DULY LINED WITH PAPER PACKING WATER PROOF) EACH CARTON SHALL MARKED WITH THE INITIALS OF THE MANUFACTURER'S BEFORE DESPATCH EACH PACKING CASE SHALL BE LEGIBLY AND INDELIBLY MARKED WITH THE FOLLOWING DETAILS:-

- I) NOMENCLATURE, CAT No OF THE STONE & THE YEAR OF MANUFACTURE,
- II) TOTAL No. OF PACKING CASES & THE No. OF THE INDIVIDUAL PACKING CASE IN A CONSIGNMENT.
- III) No. OF CARTONS IN EACH PACKING CASE & THE QUANTITY IN EACH CARTON.
- IV) MASS OF THE PACKING CASE IN kg.
- V) ADDRESS OF THE CONSIGNEE.
- VI) ADDRESS OF THE CONSIGNOR.

Handwritten signature

R.No.	DATE	ZONE	AUTHORITY	BRIEF RECORD	0%	PGD
-------	------	------	-----------	--------------	----	-----

DRN S.C.SHARMA	DRD	MATERIAL: AUSTENITIC STAINLESS STEEL	ADRDE, AGRA
CHD 5%	<i>Handwritten initials</i>	GRADE 304 (18% Cr 10% Ni) IS: 211-1972	APPROVED
TRD	PGD	FINISH: TO BE SMOOTHLY FINISHED & POLISHED BRIGHT.	
COMP	PROJ. OFFR	HEAT TREATMENT: HARDNESS: RANGE - 195/235 BHN.	 PROG. DIRECTOR (Q.A.) DRG No. ADRDE/1390
SCALE: 2:1	DIV. HEAD	CROSS CONNECTOR STRAP SAFETY PIN (PILOT PARACHUTE PSM SERIES)	
DIMENSIONS ARE IN MM			
TOLERANCE IS: 210.2 (PL J) MEDIUM			