



MATERIAL :- STEEL WIRE TO IS: 1570-1961, DESIGNATION C55.

HARDNESS :- 250-300 VHN.

FINISH :- TO BE FINISHED SMOOTH AND CADMIUM PLATED TO A THICKNESS OF 0.012 mm AND CHROMATE PASSIVATED AS PER SPECN. IS: 1572-1968, Cd-12.

TOLERANCES :- ± 0.4 mm, EXCEPT ON WIRE DIA.

PACKING :- EACH PIN SHALL BE WRAPPED IN TISSUE PAPER AND 20 NOS. THUS WRAPPED BE PACKED IN A SUITABLE CARTON. 10 SUCH CARTONS SHALL BE PACKED IN A C.W.P. (DULY LINED WITH PAPER PACKING WATER PROOF). EACH CARTON SHALL BE IDENTIFIED BY A LABEL SHOWING NOMENCLATURE AND CAT. NO. OF THE STORE AND ALSO THE TRADE-MARK/INITIALS OF THE MANUFACTURER AND YEAR OF MANUFACTURE. EACH CARTON SHALL BE MARKED WITH THE INITIALS OF THE MANUFACTURER.

BEFORE DESPATCH EACH PACKING CASE SHALL BE LEGIBLY AND INDELIBLY MARKED WITH THE FOLLOWING DETAILS:-

- (i) NOMENCLATURE, CAT. NO. OF THE STORE AND THE YEAR OF MANUFACTURE
- (ii) TOTAL NUMBER OF PACKING CASES AND THE NUMBER OF THE INDIVIDUAL PACKING CASE IN A CONSIGNMENT.
- (iii) NO. OF CARTONS IN EACH PACKING CASE AND THE QUANTITY IN EACH CARTON.
- (iv) MASS OF THE PACKING CASE IN kg.
- (v) ADDRESS OF THE CONSIGNEE.
- (vi) ADDRESS OF THE CONSIGNOR.

प्रति हस्ताक्षरित SCIENTIST-F (I.S. GUPTA) निदेशक, ह. वि. अ. वि. स., आगरा (A.D.R.D.E., AGRA)	दिनांक	नाम
	रूपीकन	
	प्रारूप	
	जांच	25-3-80 ✓
	रेखांकन	Mohar Kaur
	जुलना	26-4-80 ✓
वि. अ. डा. प्र. अधि.		
पैमाना - 1:1		

BRAKE PARACHUTE FOR JAGUAR AIRCRAFT

(CURVED PIN)

TAIL CHUTE SYSTEM FOR SHAMSHERA/C

विमा मिलीमीटर में (DIMENSIONS IN MILLIMETRES)
स्वीकृत
अं डाईंग सं AORDE/270

DO/122/82