USED ON
765-58-cs 202 | 1 | 1

USED ON
675-58-cs 137 | 1 | 1

∇3 Unless st'ed otherw'

07



A - A
M2 1



I
M 2:1



Ⓐ EQ.MATERIAL:- GRADE 42 Cr4 M02 TO I.S: 5517-93.

1. Blunt sharp edges.
2. Perform dimensions without deviations as per accuracy class 7, OST 1010.
3. Angular displarement of slots Γ from true position should be 1° max.
4. Perform heat treatment, HB 302 to 255 (Φ3.5 to 3.8).
5. Alternate material is 33xC and 38xC GOST 4543-71
6. Coating: Zinc-plated, 9 microns thick, chromatized oiled. Remove hydrogen embrittlement. Check dimensions before coating. Protect external surfaces marked by --- on section E. Coating may be absent on grooving surfaces.

196/58



00849-ICV	Ⓐ	EQ. MATERIAL ADDED
16-01-2001	ISSUE	AMENDMENTS
DC(I)No.dt		

PLEASE SEE OVERLEAF

SKETCH

765 58-312

BUSHING

45X ГОСТ 4543-71.

SHEET WEIGHT	SCALE
0.165	1:1

TOTAL SHEETS

ORDNANCE FACTORY
PROJ 1
HYDERABAD

Issue No	DCI No	NATURE OF AMENDMENTS
Ⓐ		Indian equiva material introduced.

PDC

GN Date