

SPECIFICATION

ANNEXURE - VI

C-SD OTE NO. 076ADV1920 Dt. 23/01/2020

CLOTH POLYESTER & COTTON DISRUPTIVE PATTERN (220 GSM) FOR JUNGLE WITH ARMY LOGO 152 CMS (MINIMUM) EXCLUDING SELVEDGES. SPECN NO:OCFAV/FABRIC/005 AND THAT

1) IN APPEARANCE, FEEL, FINISH AND ALL OTHER RESPECTS INCLUDING SHADE, MATERIAL SHALL CONFORM TO CORRESPONDING SEALED SAMPLES HELD IN THE CUSTODY OF CONTROLLER CUSTOMER SERVICE CENTRE, OCF., AVADI.

2) BLEND COMPOSITION SHALL BE COTTON - 80%+/-3%  
POLYESTER - 20%+/-3%.

VETTED FOR  
TECHNICAL PARTICULARS ONLY

HOS/TC

3) FIRM SHALL GET THEIR NAME WOVEN IN THE SELVEDGE WITH FINER THREAD OF SAME COLOUR AT AN INTERVAL NOT EXCEEDING 30 CMS BETWEEN TWO MARKINGS.

4) FABRIC SHALL BE WOUND IN SUCH A WAY THAT, DURING OPENING UNWINDING OF FABRIC ARMY LOGO SHOULD BE ORIENTED IN UPWARD DIRECTION ON ALL THE ROLLS.

5) WIDTH OF SELVEDGE SHALL NOT EXCEED 8 MM.

6) THE MANUFACTURER SHALL SUPPLY THE MATERIAL DULY FLAGGED FOR ALL TYPE OF DEFECTS.

7) PACKING & MARKING: AS PER CQA(T&C) KANPUR SCHEDULE NO. CQA(T&C)/PMS/35(D), EXCEPT THAT

A) FABRIC IN ROLL FORM SHALL NOT BE LESS THAN 40 METERS IN RUNNING LENGTH WITHOUT STITCHING/BASTING IN BETWEEN

B) ROLL WEIGHT SHALL NOT EXCEED 50 KGS.

C) EACH ROLL OF FABRIC SHALL BE WRAPPED SEPARATELY WITH POLYPROPYLENE PLAIN SHEET. FINAL PACKING OF 1 ROLL IN ONE WATER PROOF GUNNY/HDPE SHEET.

D) DIMENSIONS FOR PAPER TUBES OF FABRIC ROLL:

OUTER DIA - 3.5 CM, INNER DIA - 2.5 CM.

THICKNESS - 0.5 CM.

E) FABRIC SELVEDGES SHALL BE WOUND EVENLY AT ONE EDGE.

8) SELVEDGES SHALL BE FIRM, STRAIGHT AND FRINGES IF ANY SHALL NOT BE MORE THAN 5 MM.

9) SAMPLING PLAN: AS PER RELEVANT CLAUSE OF SPECIFICATION.

10) SHORT LENGTH PIECES BETWEEN 10M TO 40M SHALL BE SUPPLIED / ACCEPTED TO THE EXTENT OF 5% OF TOTAL ORDER QTY. SHORT LENGTH PIECES BETWEEN 10M TO 20M SHALL BE ACCEPTED WITH 12% PRICE REDUCTION TO COMPENSATE THE MATERIAL & LABOUR LOSS.