







FINAL DRG. FOR MFR. AT OFT
DATE 09-07-91
UP-DATED
CHECKED
F/M—PROJ.
SCT. COPY VERIFIED 10.09.91

CONTACTOR BODY

Scale 2:1. Material: casting ЛЦ-ОСТ 3-4365-79 23ХГ2МФЛУТУАЛЦ116-78. Mass: 0.2

(1) 1. Unspecified casting radii R ≈ 1 mm
2. Casting defects are permissible on finished surfaces according to reference sample
3. HRC_3 41.5 to 51.5
4. Additionally check impact strength in accordance with section 3, ГОСТ 977-75
5. Inner corners R ≈ 0.4 mm
6. Blunt sharp edges to R≈0.6 mm
7. ×Ensure sizes by tools
8. ×1Ensure size by tools not in projection
9. ×2Check sizes in relation to bases Б, В, Г, Д, Е, Ж.
10. ×3Check sizes in relation to bases Д, Е, Ж.
11. ×4Check sizes in relation to bases Д, Е.
12. Coating: cadmium plating (cadmium layer of 9 mm), F = 1.24, ACCELERATED, PHOSPHATING, WITH CHROMATE TREATMENT. EXTERNAL SURFACE: GLUE БФ-4, ГОСТ 12172-74, WITH NIGRIZINE, MARK A, ГОСТ 9307-78, ONE LAYER EXCEPT SURFACE Г.
13. MARK WITH TYPE ЛО-5, ГОСТ 2930-62.
14. MARK ЛУ, ORDINAL NUMBER OF MOULD, NUMBER OF MOULD CELL WITH TYPE ЛО-5, ГОСТ 2930-62
15. STAMP
(5) 16. MARK SERIAL NO. OF PART WITH TYPE ЛО-3 ГОСТ 2930-62

(15) (2) Knit mark is permissible within allowance limits from two sides
(3) over contour 3
(4) over contour 3
(5) 3 holes M3-6G
(6) View A
(7) 3 holes $Ø6.1A_5^{(+0.2)}$
(8) 3 holes $Ø4.7A_4$
(9) Do not blunt edges. Remove burrs
(10) Hardness test point
(11) 2 места

7		854Т-86	Втулка	2A042
6		798Т-85	Втулка	2A042
3		702Т-85	Втулка	2A041
4	*	711Т-85	Втулка	2A042
5		664Т-86	Втулка	2A042
2		555-2Т-84	Упор	2A042

(1) 2A42

2A42.07.017 2A42.07.015

Корпус

	Лит	Масса	Масштаб
	О	0,26	2:1

Копировал