

+ CONTRACTOR'S INITIAL S OR RECOGNISED TRADE MARK

NOTES

ALL JOINTS OF BODY & LID TO BE SOLDERED WITH SOLDER GRADE SN 50 CONFORMING TO SPECN IS: 193 (LATEST ISSUE)

AFTER PACKING THE LTD AND BODY ARE TO BE SEALED TO GETHER WITH TAPE ADHESIVE WATER FROOF FABRIC 38mm WIDE WITH SUITABLE LENGTH TO SPECN IND / ME / 790 (LETEST ISSUE) OR TYPE 2
PLASTICIZED PVC IS 3676 (LATEST ISSUE) PRESSURE SESNSITIVE ADHESTVE PVC TAPE WITH SUITABLE LENGTH FREE END FOLDED BACK 13mm TO FACILITATE REMOVAL

SERIAL NO REMARK OF BOX TO BE STAMPED FROM OUT SIDE ON BOTTOM LID IN 25mm LETTERING

FOR EXPLANATION OF DIMENSIONING ETC . SEL A.R.D.E. NOTE SHEET NO. 1

DIMENSION AREA IN mm THIRD ANGLE PROJECTION

MATERIAL:-

ELECTROLYTIC TIN PLATE (ETP) TO SPEC I.S. 1993 (LATES ISSUE) TIN CORTING 5.6 / 5.6 gm/m2

VARNISHING :-

THE BOX TO BE COATED INTERNELLY WITH TWO COAT OF ACP NO 225 (VARNISH SHELLAC 30% TO SPEC JSS 8010 - 63 :1991 (LETEST ISSUE)

PAINTING:-

THE BOX TO BE PAINTED EXTERNALEY WITH ONE COAT OF PAINT RED OXIDE ZINMC CROME TO SPED ISS 1 - 63 - 05 FOLLWED BY ONE COAT OF PAINT READY MIXED QUICK CRYING MATT FOR GENERAL PURPOSE BLACK TO SPEC IS 168 (LATEST ISSUE)

	D.C.I. 28813-A 1 333 / T2 22 - 2 - 68		DRAWING PROVISIONALLY SEALD DIMENSION 13.0+.5 WAS 17.8 +5 OF LID JOINT FLUSHINSIDE SHOWN ON PLANR BENDING FOR BODY SHOWN OF THE ELEVATION NOMENCLATURE & DETAIL NOMENCLATURE AMENDED NOTE RE - EMBOSSING ADDED NOTE RE - PAINTING AMENDED NOTE RE - TAPE AMENDED MATERAL AMENDED	Sd /-	
25- 7 - 67 20 - 7 - 67			TRACED WITHOUT CHANGE NOTE REGARDING SOLDERING OF BODY & LID ADDED PAINTING NOTE AMENDED		
23 - 6 - 64			TAPE ADHESIVE WATERPROOF FABRIC TO SPECN NO / ME/ 551 CLOSING THE CONTAINER PEPLACED BY TAPE WATER PROOF P.V.C. BASED TO SPECN IND / ME / 714 NOTE REGARDING INTERNAL VARNISHING OF THE CONTAINER DELETED		
DATE	AUTHORITY	ZONE	NATURE	SIG AH SP	SIG D.O

0.38

(28BG)

0.38

6.0

7.5mm LAP SEAM JONT ELUSH OUTSIDE AND TO BE SOLDERED FROM OUTSIDE

BOTTOM PIECE TO BE

SOLERED TO BODY

TO BE SOLDERED

199.0+1.5

C27A

PLAN WITH LID REMOVED

ELEVATION

TO BE SOLDERED

0.38

THE BOTTOM OF THE FOLD

SEAM JOINT TO BE NOTCHED TO
HAVE TWO FOLDS AT THE CORNERS
AFTER ASSEMBLY OF BOTTOM

STOWAGE DIMENSION IN LENGH IS 15.10.08 AMENDED AS PER DRG, NO. ISV - 353 - A 6.10.92 DC 35389 - A VARNISHING & PAINTING NOTE AMENDED MATERIAL PAINTING & VARNSHING DC 34595 - A 21.4.89 **NOTES AMENDED** 25.5.81 DCI 33173 -A Sd/-NOTES RE VARNISHING AMENDED ALL NOTES EXCEPT SERIAL NO LETTER NG 4.3.78 DCI 32597 - A AMENDED & NEW NOTE RE VEANISHING ADDED RETRACED WITH CHAMGE 28813 - A 289 - 9A 7.3.77 PREVOUS D.C.(1) NDS 29305 - A 29395 - A R. NO. DATE REVISION AUTHORITY SING

DRG SEALED 4 - 4 - 68 (PROV)
TRACED FROM C.I.A. KIRREE DRG NO ISV - 353 - A

ORDNANCE FACTORY BHANDARA BOX, C 27A TINPLATE: FOR PACKAGE AMMUNITION 92A SCALE :- 1:2 DATE :- 25 - 11 - 68 DRN :-DRG NO TCD :-Sd/-OFBA / NCP / 209 CHD :-Sd/-APPROVED BY FINAL APPROVAL

Sd/-DY. MANAGER ENGG. GENERAL MANAGER