

Spec L

SPECIFICATION (HOLOGRAPHIC)

SPEC-43

SI No		
1	L x W x H	5.6" X 2.0" X 2.5" (143X51X64mm)
2	WEIGHT	11.5 oz (325g)
3	WATER-RESISTANT	To 33 ft (10 m)
4	COLOR/FINISH	Black
5	MOUNT	1" weaver or MIL-STD-1913 rail
6	BRIGHTNESS	30 settings (10 for NV)
7	POWER SOURCE	2XAA BATTERY (SUPPORTS LITHIUM, ALKALINE OR RECHARGEABLE)
8	BATTERY LIFE (AT ROOM TEMP.)	Up to 2,500 continuous hrs (lithium) at nominal setting 12; 2,200 continuous hrs w/AA alkaline date battery life numbers
9	RETICLE OPTIONS	XR308, 68 MOA ring w/single 1MOA dot ✓

ELECTRICAL

10	BRIGHTNESS SETTINGS	20 manual daylight settings with scrolling feature (optional 10 settings for night vision use)
11	AUTO BATTERY CHECK INDICATOR	Reticle flashes on startup when battery is low
12	AUTO SHUTDOWN	User-controlled, shuts down at 4 or 8 hrs

OPERATION

13	OPTICS	Holographics
14	MAGNIFICATION	1x
15	EYE RELIEF	Unlimited
16	SEALING	Internally fog-resistant optics
17	ADJUSTMENT RANGE (PER CLICK)	Average 0.5 MOA (1/2" at 100 yards) when zeroing
18	ADJUSTMENT RANGE	Minimum +/- 40 MOA travel

HEADS-UP DISPLAY

19	OPTICAL SURFACES	Anti-reflective coating on external surfaces
20	WINDOW DIMENSIONS	1.20" x 0.85" (30mmx23mm)
21	FRONT WINDOW MATERIAL	1/8" solid glass
22	REAR WINDOW MATERIAL	3/16" thick glass laminate
23	FIELD OF VIEW	(100 yards) 30 yds. (28m) at a 3" (76.2 mm) eye relief

FOX TRADE CORP

Date of Issue 10/03/2024

Rji