






A	DRC. NO. SK-6513/TE							
1	2	3	4	5	6	7	8	
Hole / mm D								
	20 - 7.23							
B								
C								
D								
E								
F								
G								
H								
A		D.A. NO.						
$\sqrt{Rz} 70$		$\sqrt{Rz} 20 (\checkmark)$						
B		<i>Mart 2012</i>						
C								
D		1. Unspecified cast rounding radii of inner and outer angles from R0.5 to R1 mm.		2. Position, size and quantity of cast defects should not exceed those specified by control sample.		3. Pattern draft angles not greater than 1° increasingly.		
E		4. Traces from electrodes up to minus 0.3 mm.		5. Outline displacement at point of mold split is not greater than 0.2 mm.		6. 38...45 HRC At hardness test point local smoothing of surface is allowed at depth up to 0.2 mm.		
F		7. Unspecified tolerance according to ГОСТ 45-1C5 ТУ/E2		8. Coating is Chem. Phos. chrlmpreg with $\text{D}\varnothing 4$ glue GOST 12172-2016 with nigrasine grade A GOST 9307-78.		9. Stamp.		
G								
H								
A-A		M6-7H						
A		20						
B		20						
C								
D								
E								
F								
G								
H								
A		DRAWN SEEN BY CHECKED		DATE 06-06-2023		APPROVED		
B		SK-6513/TE		SHT. 1 OF 1				
C								
D								
E								
F								
G								
H								
A		7.62X39mm AR-SAF		NUT				
B		MATERIAL:- CASTING 116Л 45-1C5 ТУ/E2		50Л30 GOST 977-88				
C		0.1 M						
D		SCALE NTS		SMALL ARMS FACTORY				
E		KANPUR						
F								
G								
H								