



ΔPC	5
Δ(NF-PC)	5
UNIFORMITY	5
DOUBLE REFRACTION	4
ATTENUATION	3
NON-STRIATION	*
BUBBLING	7E
N	
Δ N	
P	VII
8	3'30"

MATERIAL: GLASS LK 105 (478656)  
GOST 3514-76E

1-CHAMFER ON RIBS 1-05, X45°.

2-NON-STRIATION AND REST OF THE TECHNICAL REQUIREMENTS ARE AS PERTY 3-3-844-78.

आयुध निर्माणी  
 ORDNANCE FACTORY  
 देहरादून  
 DEHRADUN

DRG. SK Thepliyal  
 8703  
 723  
 44-  
 APPROVED  
 W.M.P.S.

GLASS SAFETY WITH ELECTRICAL HEATER, SE - 15  
GLASS PLATE  
 DRGN<sup>o</sup>  
 AUB.640.023  
 जुमाइका नाम TITLE OF  
 संकिया OPERATION  
 CAT PART N<sup>o</sup> 1240-002441  
 AMENDMENTS  
 010/D.O./002

DR. 15-4-99  
 घातु/सामग्री  
 MATL  
 AS ABOVE  
 शीटों  
 SHEETS-1  
 SCALE 1:1  
 व्यवहार  
 TREAT  
 AS ABOVE  
 प्रति संख्या  
 SHT. NR - 1  
 DRGN<sup>o</sup>  
 MCT-1659