



FREE END OF CORDAGE TO BE HEAT STIFFENED
AFTER KNOTTING ON ASSEMBLY

NOTE:-
FOR USE WITH - RIFLE SNIPER 7.62 mm.
(SVD/SVDN) AS ALTERNATIVELY USED
IN PLACE OF "SCOURER (PULL THROUGH)"
TO PART NO. 92156-10-212-C6.4

CERTIFIED COPY OF THE
STORE DRG/GAUGE DRG/Sch/
SPEC/NOTE SHI.
Reef
DATE: 12-04-16 AOD 9

SCHEDULE OF PARTS			
DS. CAT. NOS.	DESIGNERS REF.	NOMENCLATURE	NO. OFF.
1005-001761	CISA1335/1	CORD NYLON	1
1005-001762	CISA1335/2	WEIGHT	1

26510	09.06	01-3	NOTE ADDED	DT. 3.5.94 U.C.D.O	SCALE: 1:2	SEALED: D.C. No.	QA(SA) ICHAPUR
22520	2-5-91		PROFORMA CONVERTED TO 1/2 SIZE NEG. RE-134C/80 ADD DIA. RE-134C/80	DT. 3.5.94 U.C.D.O	SCALE: 1:2	SEALED: D.C. No.	NEG. RE-TRACED DESIGNER'S REF.
SA			PREVIOUS D.C. (I) NOS. 10781-SA 11891-SA X 1428X-SA	DT. 3.5.94 U.C.D.O	SCALE: 1:2	SEALED: D.C. No.	DESIGNER'S REF.



PULL THROUGH, 1A
(NYLON)

1005-001760