


## TECHNICAL PARTICULARS FOR SHEATH NYLON 30 MM, BRAIDED

Sl No.	Test parameters	Specified values	Test Method
1	Width, mm	30-35	IS: 1954
2	Thickness, mm, max (at 200 g/cm <sup>2</sup> Pressure)	2.2	IS: 7702
3	Mass, g / m, max	46.0	IS: 7071 Part - II
4	Linear Density of Yarn, Tex x Ply [tolerance (-) 3 to (+) 8%]	46.7x3	IS: 3442
5	Constructional Parameters a. No. of Spindles b. No. of ends/spindle c. Total no. of ends	64 3 192	IS: 7071 Part - I to III
6	Plaits/dm	38±2	IS: 4227 Annex. 'D'
7	Yarn Twist per meter, TPM Single Ply	200±10% 100±10%	IS: 832
8	Material	Bright, High Tenacity, Multifilament, Nylon 6/Nylon 66 Yarn	IS: 5762
9	Construction	Braided, Coreless	Visual

**Note:** These technical particulars are tentative and these may undergo certain amendments during development, if required.



Prasanta K. Mallik  
Scientist 'D'



Gaurav Singh  
Scientist 'E'  
DH, TG(TE)



S. K. Pal  
Scientist 'G'  
GD, TG(TE)