

Nr.	Ant.	Andringens art	Datum	Inf.	Godk.	<p>Denna ritning forbliver var erendom. Att utan vart medgivande mangfaldiga. forevise. utlamna eller eljest obehorigen anvanda densamma ar forbjudet och beivras med stod av lagen den 30 maj 1919 samt lagen den 29 maj 1931 jamte andring den 22 maj 1942.</p> <p>LINDESBERGS INDUSTRI AB</p>
0		Ny farn	860516	Iah		

COVER WILL BE PHOSPHATED IN ACCORDANCE WITH SPEC.JSS 0465-01-1988 OR COATED WITH PRIME COAT PAINT READY MIXED QUICK DRYING
MATT FINISH FOR GENERAL PURPOSE RED OXIDE (ISC.446 TO IS:5-1978 REAFFIRMED IN 1991)
CONFORMING TO SPEC. IS:168-1973 REAFFIRMED IN 1988 WITH AMENDMENT No.3 FOLLOWED BY A COAT OF PAINT OLIVE GREEN (ISC:220 TO IS:5 1978 REAFFIRMED IN 1991) TO SPEC. IS:168-1973
REAFFIRMED IN 1988 WITH AMENDMENT No.3 METHOD OF APPLICATION
FOR RED OXIDE & PAINT OLIVE GREEN IS BY BRUSHING/SPRAYING/DIPPING.

DATE

5-5-94

AUTHORITY

DC.35707-A

REVISION

PAINTING NOTE AMENDED

AHSP. D.O. SIGN.

Ytbehandi/Surface conditioning
Forbehandlsa och malas ut-och invandigt
Ytfarg oliv gron 600 enl FSD 7211. W6-9
Preparing and painting on all surfaces

8-10-93	D.C.35603-A	PAINTING NOTE AMENDED			APPROVED FOR CQA(A)
7-1-93	D.C.35436-A	PAINTING NOTE AMENDED			
18-1-88	DC(I) 34306 - A	DRG. PROV. SEALED.			
DATE	AUTHORITY	REVISION	AHSP.	D.O.	AHSP:- CQA(A) KIRKEE
			SIG.		
2	1	Lock Amne Cover Workplece			13602
1	1	Kupol/Cup			13601
Det.	Ant.	Benamning	Material	Dimension	Anmarkning
Tillatna mattavvikelser nar tolerans ej direkt utsatts SMS 715			Ytjamnhet dar ej. annat angetts		ISO toleranser SMS ritningsregler
Dat.	Rit.	Godk.	Skala.	Ersatter L4 - 13600	
850319			1:2.5	Ersatt av	
 LINDESBERGS INDUSTRI AB			Lock/Cover Grupp CHG PORP M4A2		13600-0-0