

REVISION		MATERIAL NOTE AMENDED
AHSP.	D.O.	
SIGN.	D.O.	

Den plomberade benattaren skall motsta min 20 kpa (0.2 bar)

Lufttryck under 15 sek utan lockage


Smärj in pluggens ganga med grafitfett efter prov.

LEAK TEST AS PER SPEC. IA 1169 (n)

Test plug shall be coated lightly with soft graphite grease after testing.

5-5-94	DC 35707-A	LEAK TEST SPEC. UPDATED.		
14-3-91	DC 35050-A	NOT 'SEALED CONTAINER 15 SECONDS MINIDLETED AND 'LEAK TEST' (LATEST ISSUE ADDED)		
23-11-87	DC.I. 34274-A	DRG. PROV. SEALED.		
DATE	AUTHORITY	REVISION	AHSP.	D.O.

APPROVED		FOR CQA(A)
AHSP.- CQA(A) KIRKEE		

6	1	Etikett/Label			ent order ftu	
5	1	Blyplomb/Lead seal				
4	1	Papp/Wrapper			13607	
3	1	Distans/Spacer			13980	
2	1	Laddning/Charge Drop			enl order ftu	
1	1	Embutub/Container M13A2			13583	
Det.	Ant.	Benamning			Material	Dimension
Tillåtna måttavvikelser när tolerans ej direkt utsatts SMS 715					Yfamnhet där ej. annat angetts	
Dat.	Rit.	Godk.	Skala.		Emballagetub, packad Container, packed	
86.05.05			1:2.5			
 LINDEBERGS INDUSTRI AB					Grupp	M4A2
					LNG/CHG PORP	
					13979-0-0	