R15 FOR 4 BOSSES
R15 для 4-х приливов

7 ALONG CONTOUR

Тип 1 ГОСТ 1412-79

1. DRAFTS SHOULD NOT EXCEED 1 : 20 TOWARDS THE EXTERNAL SIDE. UNSPECIFIED RADII SHOULD NOT EXCEED 5 mm.
2. COMPONENT SHOULD MEET THE REQUIREMENTS OF GENERAL PART 172 TY6 FOR NON-FERROUS CASTINGS.
3. HEAT TREATMENT SHOULD BE CARRIED OUT AS PER MODE T5 ACCORDING TO GOST 1583-75.
4. UNSPECIFIED CASTING DIMENSIONS SHOULD BE CARRIED OUT WITH ACCURACY ± 2 mm.
5. MARK THE MATERIAL ON ANY UNMACHINED SURFACES BY PUNCHING OR CASTING TYPE П 0-5 GOST 2930-62.
6. MAY BE MANUFACTURED ALONG DOTTED LINES.

M-M
TURNED

A-A
TURNED

Для 3 отв.
for 3 holes

			172.25.001-1		
			CASTING HOUSING LOWER	SHEET 1 of 3	1:1
ISSUED	DATE	SIGNATURE			
CHECKED			AL9 GOST 2685-75	HEAVY VEHICLES FACTORY	