



- (i) BODY :
(ii) CLIP : }

CARBON SPRING STEEL EN-42 J AS
PER BS: 970 - 1955

2 - HARDNESS :-

HV 375-400

3 - FINISH :-

TO BE SMOOTHLY FINISHED WITH
ROUND EDGES AND NICKLE -
CHROMIUM PLATED TO IS: 1068-1968,
SERVICE GRADE No.3, (SNI 406 CXX)

4 - PROOF LOAD :- (P) 910 kgf

5 PACKING:- EACH COMPONENT SHALL BE WRAPPED IN A TISSUE PAPER AND 25 Nos. THUS WRAPPED BE PACKED IN A SUITABLE CARTON. 10 SUCH CARTONS SHALL BE PACKED IN A CWP (DULY LINED WITH PAPER PACKING WATERPROOF). EACH CARTON SHALL BE MARKED WITH THE INITIALS OF THE MANUFACTURER. BEFORE DESPATCH, EACH PACKING CASE SHALL BE LEGIBLY AND INDELIBLY MARKED WITH THE FOLLOWING DETAILS:-

- (i) NOMENCLATURE, CAT No. OF THE STORE AND THE YEAR OF MANUFACTURE.
- (ii) TOTAL NO. OF PACKING CASES AND THE NO. OF INDIVIDUAL PACKING CASES IN A CONSIGNMENT.
- (iii) NO. OF CARTONS IN EACH PACKING CASE AND THE QUANTITY IN EACH CARTON.
- (iv) MASS OF THE PACKING CASE IN kg.
- (v) ADDRESS OF THE CONSIGNEE.
- (vi) ADDRESS OF THE CONSIGNOR.

DRN	material	DRD	MATERIAL :- AS SPECIFIED ABOVE	ADDRDE, AGRA
CHN	signature	Qty	FINISH :- AS SPECIFIED ABOVE	
TRD		PGD		
COMP		o/c	HEAT TREATMENT :-	APPROVED
DIMENSIONS IN MILLIMETRES		PROJ. OFFR. DIV. HEAD		
SCALE :- 1 : 1		CONNECTING LUG LARGE BMK-41 PARACHUTE		
TOLERANCE :- 13 : 2102 (Pt 1) MEDIUM				
		PROG. DIRECTOR (C) DRG. No. ADDRDE/1305 (3) DRD/48/98		