

(Page No. – 2)

4) Metallic Valve Body:

Standard Metallic Valve Body to suit on the wheel rim with Run Flat System fitted for filling of air for tube less tyre.

NOTE: 1. Dimensions mentioned in brackets are for reference only.

2. It is mandatory for the supplier to ensure that Make, Model Number, batch Number, Month and Year of manufacture is embossed on the side wall of Run Flat.

III INSPECTION:

GM / VFJ or his authorized representative at VFJ.

IV TESTING PROCEDURE / ACCEPTANCE CRITERIA:

The two run flat system assy samples supplied by the firm shall be fitted diagonally on Mine Protected Vehicle. After firing of two bullets from 7.62 SLR on the side wall of each tyre from a distance of 10 meters, the vehicle should run at a minimum speed of 50 KMPH for a distance of first 10 Kms and at a speed of above 40 KMPH for a distance next 30 Kms minimum on Black Top road after deflation of tyre. The sample shall be considered acceptable, if vehicle completes 40 Kms run satisfactorily as above without losing control of the vehicle and run flat system getting dislocated from the Rim. If any one sample or both the samples fitted does not meet this requirement the sample shall be considered not acceptable.

Minimum one set consisting of two Run Flat System Assemblies out of every 100 nos. or part there of for each consignment against supply order shall be subjected to testing as above. Firm has to provide free replacement of the quantity so consumed in the trials/testing. Incase the Run Flat System Assemblies fails in the trials/ testing, the whole lot will be rejected.