

MAGNESIUM POWDER GRADE 'B' TO SPECN. NO. IS : 2307:1977
(FIRST REVISION) AMENDMENT NO.1 - 1986 (REAFFIRMED 1991) TO
FOLLOWING SIEVE SPECTRUM:-

1. RETENTION ON 30 BSS	-	NIL
2. RETENTION ON 44 BSS	-	15 TO 17%
3. RETENTION ON 100BSS	-	98 TO 100%

APPARENT DENSITY 0.9 ABOVE

MAGNESIUM POWDER SHOULD BE MANUFACTURED BY CUT
METHOD AND NOT BY BLOWN OR ATOMISED

PACKING :

MATERIAL TO BE PACKED IN POLYTHENE BAG BEFORE
PACKING IN 50KG/ 200 KG CAPACITY PLAIN STEEL DRUMS WITH
EXPENDABLE LIDS (DRUMS SHOULD BE CLEAN & FREE FROM RESIDUAL
FLUX)

VETTED as per GM approual Dt 04-12-17
(ref NOTING no. 411/14, Dt 03.12.2007)
Copy enclosed h/w.


JWM/STD. CELL

WJM/PL - To advise
whether new approual
of existing JGM/III & GM
required for further
processing.
As a GM approual encl-
is Dtd 2007
WJM/PL 22/11/2020
said same sanction to be
used.

HOS/MCO