



TABLE OF DIMENSIONS

SIZE	A	B
180	180±2	12
140	140±2	12

MATERIAL:- SPRING STEEL STRIP TO B.S:1449-EN-43G

WORKMANSHIP AND FINISH:- TO BE SMOOTHLY FINISHED,
CADMIUM PLATED TO A MINIMUM THICKNESS OF .012mm
AND CHROMATE PASSIVATED TO SPECN. IS:1572-1968,cd-12

EMBRITTLMENT RELEASE:- STRIPS,AFTER CADMIUM PLATING AND
PRIOR TO CHROMATE PASSIVATION, SHALL BE MAINTAINED
AT A TEMP. 150°C TO 200°C FOR HALF AN HOUR MIN. TO
REMOVE HYDROGEN EMBRITTLMENT.

PACKING:-

ONLY ONE TYPE OF STRIP SHALL BE PACKED IN ONE CARTON/C.W.P EACH STRIP SHALL BE WRAPPED IN TISSUE PAPER AND 50 Nos. THUS WRAPPED BE PACKED IN A SUITABLE CARTON. 10 SUCH CARTONS SHALL BE PACKED IN A C.W.P (DULY LINED WITH PAPER PACKING WATER PROOF.)

EACH CARTON SHALL BE MARKED WITH THE INITIALS OF THE MANUFACTURER. BEFORE DISPATCH EACH PACKING CASE SHALL BE LEGIBLY AND INDELIBLY MARKED WITH THE FOLLOWING DETAILS-

- (1) NOMENCLATURE, CAT.No. OF THE STORE AND THE YEAR OF MANUFACTURE.
- (2) TOTAL No. OF PACKING CASES AND THE No. OF INDIVIDUAL PACKING CASE IN A CONSIGNMENT.
- (3) No. OF CARTONS IN EACH PACKING CASE AND THE QUANTITY IN EACH CARTON.
- (4) MASS OF THE PACKING CASE IN Kg.
- (5) ADDRESS OF THE CONSIGNEE.
- (6) ADDRESS OF THE CONSIGNOR.

SCALE:- N T S	A D R D E AGRA	DRN.	C.P.PAL	<i>Handwritten Signature</i> PROJ. OFFR./GROUP OFFR.
DIMENSIONS IN mm	GROUP- PAS	CHD.	NIROTI	
TOL:-	(STRIP METAL 180mm & 140mm) D. 10 (RESERVE)			APPROVED
MATERIAL:- AS ABOVE				<i>Handwritten Signature</i> PROJ.DIR./GROUP DIR.
FINISH:-				