



MATERIAL :- EN-24 TO SPECN BS:970

WORKMAN SHIP :- BURR, ROUGHNESS AND EDGE SHARPNESS SHOULD BE REMOVED AND FINISHED SMOOTH.

FINISH :- TO BE FINISHED SMOOTH, CADMIUM PLATED TO A MINIMUM THICKNESS OF 0.012mm AND CHROMATE PASSIVATED TO SPECIFICATION IS: 1572-1968, Cd-12.

PACKING :- EACH PULLY SHALL BE WRAPPED IN TISSUE PAPER. 10 Nos THUS WRAPPED BE PACKED IN A SUITABLE CARTON. 20Nos OF SUCH CARTONS SHALL THEN BE PACKED IN C.W.P. (DULY LINED WITH PAPER PACKING WATER PROOF). ONE PULLY IN A EACH CARTON SHALL THAN BE IDENTIFIED BY A LABEL SHOWING CAT. No. DESIGNATION OF THE STORE AND ALSO THE RECOGNISED INITIALS OF THE MANUFACTURER. EACH CARTON SHALL BE MARKED WITH THE INITIALS OF THE MANUFACTURER. THE PACKING CASE SHALL BE LEGIBLY AND INDELIBLY MARKED WITH THE NAME OF ITEM ADDRESS OF THE CONSIGNEE, CONSIGNOR TRADE MARK, CAT No., DESIGNATION OF STORE, YEAR OF MANUFACTURE, QUANTITY AND NUMBER OF THE INDIVIDUAL PACKS.

GENERAL TOL :- ± 0.2 WHERE OTHER WISE NOT SPECIFIED.

MFG. PROCESS :- GENERAL ENGINEERING METHOD

SCALE :- 1 : 1
DIMENSION IN mm
TOLERANCE--IS:2102-1993
FINISH :- --
HEAT TREATMENT :- --

ADRDE, AGRA	DRN.	PRD. OFF.
GROUP :- CP(H.D. SYSTEM)	CHD.	GP.DIR.
PULLEY HEAVY DROP P'CHUTE (P-7 PLATFORM) SYSTEM FOR IL-76 A/C		DI/cD&S
		APPROVED
		HEAD(PARA)
		DRG.No.:--ADRDE/ 1.6.01.01.06-02

DI/cD&S
APPROVED
HEAD(PARA)
DRG.No.:--ADRDE/ 1.6.01.01.06-02

Sl. No.	DATE	ZONE	AUTHORITY	BRIEF RECORD	DI/c D&S	HEAD QA
1						
2						
3						
4						

