

Annealed-B

SET OF EBXL CABLE

DESCRIPTION	Qty. in metres per set
4 x 2.5 sq. mm., Electroplated annealed tinned copper flexible copper conductor with Halogen free fire retardant EBXL dual layer Polyolefin compound insulation and annealed tinned copper braided collectively screened cable with maxi. outer dia. 12 mm; conforming to EED 50-12 Part Number 6145021150 (Table 29)	420
3 x 1.0 sq. mm., Electroplated annealed tinned copper flexible copper conductor with Halogen free fire retardant EBXL dual layer Polyolefin compound insulation and annealed tinned copper braided collectively screened cable with maxi. outer dia. 10 mm; conforming to EED 50-12 Part Number 6145021132 (Table 29)	1020
2 x 4 sq. mm., Electroplated annealed tinned copper flexible copper conductor with Halogen free fire retardant EBXL dual layer Polyolefin compound insulation and annealed tinned copper braided collectively screened cable with maxi. outer dia. 12.3 mm; conforming to EED 50-12 Part Number 6145021120 (Table 29)	260
37 x 0.5 sq. mm., Annealed tinned copper, halogen free polyolefin + LFH dual layer EBXL insulated, cores laid up, collectively screened & FR LSZH EBXL polyolefin sheathed flexible cable with maxi outer dia. 23 mm; conforming to EED 50-12 Part No. N6145 - 021167 (Table 29)	420
12 x 0.5 sq. mm., Annealed tinned copper, halogen free polyolefin + LFH dual layer EBXL insulated, cores laid up, collectively screened & FR LSZH EBXL polyolefin sheathed flexible cable with maxi outer dia. 14.3 mm; conforming to EED 50-12 Part No. N6145 - 021159 (Table 29)	680

S-397000113

Quantity
Wm TCR

L'F: 7107006031