QUALITY ASSURANCE PLAN (SRCG IM PHASE)									Issue No : 01 Rev No: Date of Issue
									05 /06 / 2021
Drg . No.	nmenclature PIN KEY								_
Nommenclature									OFT/QAP/SRCG/066425A
Material									
Component Nomenclature/ operations	Charateristics	Class	Type of check	Quantum of check	Reference document	Acceptance norms	Format of record	Inspection by QAE(N), Chennai or by Nominated Agency (Review/Witness)	Remarks
Pin Key (Raw material)	General appearance	Non Critical	Visual	100%	Alloy Steel Bar Rnd SAE 4130 Normalised as per	As per Alloy Steel Bar Rnd SAE 4130 Normalised as per SAE-AMS-S-6758 OR SAE 4340 Normalised as per SAE-AMS-S-5000.	Firm Inspection report	R	Sample will be drawn and sealed by Inspection Agency
	Chemical properties	Non Critical	Chemical Lab analysis	100%	SAE-AMS-S-6758 OR SAE 4340		NABL lab	R	
	Mechanical properties	Non Critical	Mechanical Lab analysis	100%	Normalised as per SAE-AMS-S-5000.		Test report from NABL lab	R	
In process -Turning, Milling,Threading	Dimensions Specified in the Inspection report of the component	Non Critical	Dimensional measurement	IS 2500 Level II AQL 2.5%	''	As per Approved Drg No. 066425A-00	Firm Inspection report	W	Firm will be undertaking 100 % Checks and Pre inspection Report for the same be submitted
Dry Film Lubrication in a FluoroPolymer Organic Resin Class 2 colour Matte Black Type 1	General appearance	Non Critical	Visual and Dimensional Checks	IS 2500 Level II AQL 2.5%	Approved Drg No.	5-13 Micron Thick per VS-1-3-1-165 (or equivalent)	Firm Inspection report	W	
Phosphate Coating	General appearance	Non Critical	Visual and Dimensional Checks	IS 2500 Level II AQL 2.5%		Approved Drg No. 066425A-00	Firm Inspection report	W	
Final Inspection	General appearance	Non Critical	Visual and Dimensional Checks	IS 2500 Level II AQL 2.5%		As per Approved Drg No. 066425A-00	Firm Inspection report	W	