

SPECIFICATION AGAINST C-OTENO-056 ADVI 920 Dt. 03/12/2019

POLYESTER MESH INTERLINING FABRIC OG - 142 CM WIDTH
(EXCLUDING SELVEDGES). SPECIFICATION.

- 1) THE MATERIAL SHALL BE 100% POLYESTER.
- 2) MASS / SQ. MTR - 110 +5/-3 GRAMS.
- 3) MESH DENSITY - 45 HOLES/SQ INCH (MIN).
- 4) BURSTING STRENGTH - 7.0 KGF/SQ CM (MIN).
- 5) COLOUR FASTNESS TO WASHING : IS/ISO 105-C10:2006
TEST NO C(3) a) COLOUR CHANGE - 4 OR BETTER
b) STAINING ON COTTON - 4 OR BETTER
- 6) COLOUR FASTNESS TO PERSPIRATION (BOTH ACIDIC & ALKALINE)
AS PER IS:971.
a) COLOUR CHANGE - 4 OR BETTER.
b) STAINING ON COTTON - 4 OR BETTER.
- 7) COLOUR FASTNESS TO LIGHT AS PER IS:2454 - 4 OR BETTER.
- 8) THE MANUFACTURER SHALL SUPPLY THE MATERIAL DULY FLAGGED
FOR ALL TYPE OF DEFECTS.
- 9) WIDTH OF SELVEDGE SHALL NOT EXCEED 15 MM.
- 10) FIRM SHALL GET THEIR NAME/ TRADE MARK, BATCH NO & YEAR
OF MANUFACTURE STAMPED IN THE SELVEDGE WITH A DISTANCE
OF ONE METER BETWEEN MARKINGS.
- 11) PACKING & MARKING: AS PER CQA(T&C) KANPUR SCHEDULE NO.
CQA(T&C)/RMS/35(D), EXCEPT THAT
A) MATERIAL SHALL BE SUPPLIED IN FOLDED FORM NOT LESS
THAN 40 METERS IN RUNNING LENGTH WITHOUT STITCHING/
BASTING IN BETWEEN.
B) THAN WEIGHT SHALL NOT EXCEED 50 KGS.
- 12) SAMPLING PLAN : AS PER ANNEXURE (ISO-2859).

VETTED FOR

TECHNICAL PARTICULARS ONLY

HOS/TC