	WORM	GEAR TO DE	RG NO 176.23.022	SB-1SB & WORM 176.23.051 AND WOR	M WITH WORM GEAR HVF.23.0)62SB	
SI no.	Nomenclature & drawing No.	Manufacturing / Inspection		Must be possessed by the vendor in his premises (P&M list and testing / inspection equipment list to be submitted)	May be possesed by the vendor in his premises or out sourced (Self declaration to be submitted)	FIRM Comp- liance (Y/N)	Remarks
	176.23.022SB-1SB Worm Gear 176.23.051 Worm	TECHNOLOGY-1	Raw material	·	Firm should be capable to arrange the raw material like forging, bar material, Brass moulded casting etc as per drawing specification and standard.		
	(Items 1 & 2 to be ordered together to get the supplies as a pair)	TECHNOLOGY-2	Turning	CNC Turning machine suitable to accommodate component upto 200 mm diameter with 0.050mm accuracy			
_	HVF.23.062SB Worm with Worm Gear		Grinding	Internal,External & Surface grinding machine as per component Dia 200mm with 0.010mm accuracy			
			Gear machining	Worm Gear machining facility of module 4 or more as per drg specification	Gear Shaping facility of module 2 or more as per component requirement with DIN class 7 accuracy		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
			Worm & Worm Gear Lapping	Firm should have the Lapping facility for both Worm & Worm Gear and should be supplied as a pair (OR) Firm should submit the undertaking in this regard that they will create the facilities within 6 months from the date of receipt of order.			
		TECHNOLOGY-3	Heat Treatment		Carburising, Hardening, Induction Hardening & Tempering furnace with Oil quenching facility suitable to the components		,
, 119 see	CK		Protection coating	Δ	Oxidising or Oxido Phospahting facility suitable to the component	. Commence	

SI no.	Nomenclature & drawing No.	Manufacturing technology & Testing / Inspection Facilities required to produce the item		Must be possessed by the vendor in his premises (P&M list and testing / inspection equipment list to be submitted)	May be possesed by the vendor in his premises or out sourced (Self declaration to be submitted)	FIRM Comp- liance (Y/N)	Remarks
2		TEST / INSPECTION-1	Surface Roughness Tester		Surface Roughness Tester for Ra &Rz values		
33	(Items 1 & 2 to be ordered together to get the supplies as a pair) HVF.23.062SB Worm with Worm Gear		Gauges	Standard Gauges for checking the Worm & Worm gear suitable to the requirement of the components (OR) Firm should submit the undertaking in this regard that they will create the facilities within 6 months from the date of receipt of order.	·		
				Vernier Caliper, Micrometer. Gear tooth Micrometer, Radius gauge, Feeler Gauge etc. suitable to the requirement of the componentsFirm should submit the undertaking in this regard that they will create the facilities within 6 months from the date of receipt of order.	,		
		TEST / INSPECTION-2	Hardness measurement	,	Brinell & Rockwell Hardness Tester		

Note: Justification for alternate facilities may be shared to prove that alternate facilities can be utilised to manufacture the item wherever the facilities are mentioned above are not available, but vendor has alternate facilities.

1. Perfect Gears, Chennai

Likely Sources: 2. Sakthi Tech , Coimbatore

3. Santhi Gears, Coimbatore